



ER-900 Series

Multi-Use ECRs from the World's Leading ECR Builder

Features

- Choose a flat keyboard model for food service or a raised keyboard model for retail environments.
- Two-line alpha-numeric display shows each item as it is entered.
- Connects to popular POS peripherals.

Best Applications

- Food Service: Quick Service, Sandwich, Ice Cream, Deli, Cafeteria and Concessions
- Simple Table Service: Diners, Asian and Ethnic Restaurants, Bar & Grill
- Independent Retail Merchants, Especially Simple Retail Scanning
- Simple Franchise Concepts



SAM4s ER-940 shown with optional card reader.



ER-920

Flat Spill-Resistant Keyboard; Receipt Printer



ER-940

Flat Spill-Resistant Keyboard; Receipt And Journal Printers




ER-925

Raised-Key Keyboard; Receipt Printer



ER-945

Raised-Key Keyboard; Receipt And Journal Printers



Keyboard

The programmable keyboard can be customized with PLU keys for open price or preset entries and function keys for discounts, payments and corrections.

- Models with the 150 key position flat keyboard support 100 or more PLU locations.
- Raised keyboard models feature 21 standard PLU locations, expandable to 63 or more PLU locations.

Thermal Printer

Keep pace with fast, quiet, thermal printing. Drop-in loading simplifies paper changing and virtually eliminates paper jamming.

Electronic Journal

Merchants selecting the ER-920 or ER-925 without a traditional journal printer can save or print an electronic sales journal. Electronic journal is available on all models, allowing you to quickly search and investigate transaction-level information.

Convenience and Accuracy

Save time with simplified procedures that ensure accuracy at check-out time. Standard features include:

- Cancel Sale Function
- Keylock Controlled Transaction Void
- Complete Receipt on Request
- Check Cashing
- Post Tendering
- Four Automatic Currency Conversion Keys

Reliable System Components

- Full Size Cash Drawer Includes Media Slots and a Removable 5 Bill, 5 Coin Drawer Insert with Adjustable Coin Dividers
- Large Easy to Read Two-Line LCD Operator Display

- Standard LED Customer Display
- Save/load your program, load receipt logos/images or update firmware by SD card.

Standard RS-232C Communication

The affordable SAM4s ER-900 series provides the gateway to system features using two standard RS-232C communication ports. Two additional ports are available for: direct or modem PC communications with optional polling software; kitchen printer; slip printer; scale; scanner; pole display; coin dispenser; Datatran™ integrated credit; kitchen video; video surveillance.

Additional Features

- Up to Approximately 2,000 PLUs that can be Accessed Directly Through Individual Keyboard PLU Keys or Indirectly Through the PLU Look-Up Key
- Automatic Tax Computation for Up to 4 Rates or Tables
- 10 Media Keys: Cash, Check and Up to 8 Charge Keys
- Up to 99 Group Totals
- Up to 50 Clerks/Cashiers
- Graphic Bitmap Logo
- Condensed Journal
- Compulsory Cash Declaration
- Hash PLU Status
- 10 One-Touch Macro Keys
- Training Mode

Management Reports

- Complete Financial Report
- Individual Clerk/Cashier Report
- Hourly Sales Analysis
- Reporting for Up to 50 Clerks/Cashiers
- PLU, Group and Stock Reports
- Period-To-Date Financial, Hourly, Cashier, Group and PLU Reports
- Sales by Day Report for 31 Days
- Open Check Report



Two-Line by 16-Character LCD Operator Screen



9-Digit LED Customer Turret Display



SD Port Hidden Under the Printer Cover is Secure from Tampering



Up to 4 RS-232C Ports Hidden Behind a Convenient, Easy to Access Door



2 Media Slot Drawer with Extra Deep Insert and Adjustable Coin Dividers

SPECIFICATIONS

Display:	2-Line Alpha-Numeric Backlit Liquid Crystal Operator Display
Rear Display:	9-Digit LED
Printer(s):	Seiko LTPD245
Printer Speed:	22 Lines per Second
Paper Roll:	2¼" (58mm) Thermal Paper
Dimensions:	15-3/4"W x 11-13/16"H x 17-3/4"D
Weight:	Single Station – 24.76 lbs.; Dual Station – 25.64 lbs.
Power Requirements:	120V AC ± 10%, 50/60 Hz
Power Consumption:	Approximately 25 Watts
Operation Temp.:	32°F ~ 104°
Humidity Range:	30% to 80% RH (Non-Condensing)
Memory Protection:	Full Charge for 24 Hours Will Protect Memory for 90 Days

All product features are subject to change without notice.
All product and company names are trademarks, service marks or registered trademarks of their respective owners.